



# P2C 250 Series

True All-in-One as KIOSK & POS in one terminal



## Design

Harmony of Solid & Sophisticated  
Design and Soft & Strong product line  
Space-saving & Slim style

+



## Stability

Outstanding heat treatment ability  
through the whole aluminum ventilation frame  
Longer life-span, Low maintenance fee

+



## Expandability / Flexibility

Abundant I/O Ports  
Wide space for I/O Port connection  
Multi Display available(3p)

+



## Easy Maintenance

Easy replacement of all main parts like  
M/B, LCD, Touch panel

+



## True All-in-One

Easy Conversion by simple assembly  
(Landscape/ Portrait)



01

Wide space for I/O Port connection



02

Outstanding Aluminum Ventilation Frame



03

One-touch type of Dual monitor connection (Patent application)



04

Luxurious metal style of Premium logo bar



**Q. Need Enough connection I/O ports? No worries!!**  
**6 Serials ports for power supply & many types of I/O ports are available.**

**Monitor upper I/O Panel**

- 1 Serial (COM1)
- 2 Serial (COM2)
- 3 Serial (COM3)
- 4 DP Port
- 5 DC 12V
- 6 LAN
- 7 USB 1 / 2
- 8 Serial (COM4)
- 9 Serial (COM5)
- 10 Serial (USB / COM6)
- 11 SSD (HDD)
- 12 Audio
- 13 USB 3 / 4
- 14 USB 5 / 6
- 15 Parallel

**Monitor bottom I/O Panel**

- 15 Parallel
- 14 USB 5 / 6
- 13 USB 3 / 4
- 12 Audio
- 11 SSD (HDD)

## Specifications

\*Specifications are subject to change without prior notice.

	S-250P	J-250P	G-250P
<b>System</b>			
Processor	7th or 8th Generation Intel® Core™ i3, i5, i7 Processors	Intel® Celeron® Quad-core Processor J1900 2.0GHz	Intel® Celeron® Quad-core Processor J4125 2.0GHz/2.7GHz
Chipset / BIOS	Intel® Kaby Lake SoC / AMI	Intel® Baytrail SoC / AMI	Intel® Gemini Lake SoC / AMI
Storage	2.5" SATA III SSD 64GB (HDD 500GB & SSD 128GB, optional)	(SATA III SSD 128GB (HDD 500GB & SSD 128GB, optional) *2.5	2.5" SATA III SSD 64GB (HDD 500GB & SSD 128GB, optional)
Memory	4GB SO-DIMM, DDR4 2133MHz x 2 (Max 32GB, optional)	(4GB SO-DIMM, DDR3 1333MHz x 1 (Max 8GB, optional)	4GB SO-DIMM, DDR4 2400 MT/s (Max 16GB, optional)
Graphics	Intel® HD Graphics 520 / Intel® HD Graphics 620	Intel® HD Graphics	Intel® UHD Graphics 600
Multi Monitor	2 (# of Displays Supported) -- up to 3 monitors	2 (# of Displays Supported)	2 (# of Displays Supported)---up to 3 monitors
Expansion Slot	1 x mini PCI-e	1 x mini PCI-e	1 x m.2 NVMe, 1 x m.2 WiFi & Bluetooth(optional)
OS	Windows 10 IoT Enterprise Value/High-End, POSReady 7	Windows 10 IoT Enterprise Entry, POSReady 7	Windows 10 IoT Enterprise Entry(SAC-20H1, SAC-20H2)
<b>Display</b>			
Primary Display Type	15" WLED Backlight (Brightness: 350 cd/m <sup>2</sup> , 1024 x 768 Resolution)		
Touch	True-Flat Capacitive 10 Point Multi-touch		
<b>I/O Interfaces</b>			
<b>Rear Top &amp; Bottom Ports</b>			
USB	6 x USB 3.0 (Rear Top x 2, Rear Bottom x 4) 1 x USB 2.0 (included RJ11 port), 1 x USB 2.0 (included DisplayPort)	6 x USB 2.0 (Rear Top x 2, Rear Bottom x 4), 1 x USB 2.0 (included RJ11 port), 1 x USB 2.0 (included DisplayPort)	4 x USB 3.0 (Rear Top x 2, Rear Bottom x 2), 2 x USB 2.0 (Rear Bottom), 1 x USB 2.0 (included RJ11 port), 1 x USB 2.0 (included DisplayPort)
Serial	6 (DB9 x 3, RJ50 x 2, RJ11 x 1) COM1, 3, 5: DB9(+5V on pin #9, selectable by BIOS), COM2, 4: RJ50 (+5V and +12V always be on pin #10 and #1), COM6: RJ11(+5V always be on pin #1)		
Parallel	1 x LPT/IEEE 1284(DB25 on Rear Bottom)		
Audio	1 x Audio-out / 3.5mm (changeable for MIC)		
Secondary Display	1 x DisplayPort (included 1 x USB 2.0 / Power Delivery +12V) *Can be used for HDMI and Standard DVI, VGA monitor by passive cable		2 x DisplayPort(included 1 x USB/Power Delivery +12V)
LAN	1 x RJ45 (Base-T 10/100/1000 Ethernet)		
<b>Peripheral Options</b>			
Secondary Display DisplayPort	LCD Type: 10" or 15" LCD (USB Port x 1), Touch Type: 10" or 15" LCD with Capacitive Touch (USB Port x 1) *P2C Smart Multi Display Functions: Supported Multi Display Function by DP MST Hub / Supported Standard HDMI, DVI, DP by each cable		
Customer Display (CDP)	VFD Type (Alphabet & Numeric, 20 characters x 2 lines)		
Card Reader (MSR / SCR)	Smart Card Reader: ISO/IEC 7816 EMV Level 1 *Interface: USB(HID) and RS232C(COM6) Magnetic Stripe Reader: ISO 7811 ID-1 All tracks		
Dallas Reader	Dallas Reader(i-button): 6 characters / prefix and suffix *Interface: USB(HID) and RS232C(COM6)		
<b>Physical Dimension</b>			
Dimension (W x D x H)	362 x 243 x 333 (mm)		
Weight	5.3 (Kg) / 11.7 (lb)		
<b>Environment</b>			
Power Supply	DC 12V/5A (AC 100V~240V, 60W)		
Temperature	Operating: 0 ~ 50°C at 10% to 90% humidity		
Certifications	CE, FCC, KC, CB		

**Software: POPs Retail**

- Option • 1 x cash drawer port (RJ11)
- Fingerprint : Yes
- Serial conversion cable : RJ45 to D-Sub9
- Speaker : 2 x 0.8W
- Wall mount kit : VESA-Compatible, 75x75(mm), 100x100(mm)